

# NONTECHNICAL SOIL DESCRIPTIONS

These descriptions describe soil properties or management considerations specific to a soil map unit and components of map units. These reports are generated from the National Soil Information System soil database for distribution to land users.

## BaA--Barclay Silt Loam, 0 To 2 Percent Slopes

Barclay component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is somewhat poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 15 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is not a hydric soil.

## BaB2--Barclay Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded

Barclay component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is somewhat poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 15 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is not a hydric soil.

## Bp--Borrow Pits

Borrow Pits component makes up 95 percent of the map unit. The assigned Kw erodibility factor is .02. The slowest permeability within 60 inches is rapid. Available water capacity is low and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 8s. This component is not a hydric soil.

## Cb--Coastal Beaches

Coastal Beaches component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .05. This soil is poorly drained. The slowest permeability within 60 inches is rapid. Available water capacity is moderate and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 36 inches. The soil has a moderately saline horizon. It is in nonirrigated land capability class 8w. This component is a hydric soil.

## DoA--Downer Loamy Sand, 0 To 2 Percent Slopes

Downer component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .20. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2s. This component is not a hydric soil.

## DoB2--Downer Loamy Sand, 2 To 5 Percent Slopes, Moderately Eroded

Downer component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .20. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2s. This component is not a hydric soil.

## DoC2--Downer Loamy Sand, 5 To 10 Percent Slopes, Moderately Eroded

Downer component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .20. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## Ek--Elkton Loam

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

Es--Elkton Silt Loam

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## Fa--Fallsington Sandy Loam

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

## Ff--Fallsington Fine Sandy Loam

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

## Fg--Fallsington Loam

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .32. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .32. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

## GaB--Galestown Loamy Sand, 0 To 5 Percent Slopes

Galestown component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .17. This soil is somewhat excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3s. This component is not a hydric soil.

## GaC--Galestown Loamy Sand, 5 To 15 Percent Slopes

Galestown component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is somewhat excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

KmA--Keyport Loam, 0 To 2 Percent Slopes

Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## KmB2--Keyport Loam, 2 To 5 Percent Slopes, Moderately Eroded

Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## KmC2--Keyport Loam, 5 To 10 Percent Slopes, Moderately Eroded

Keyport component makes up 95 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## KmD--Keyport Loam, 10 To 15 Percent Slopes

Keyport component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## KpA--Keyport Silt Loam, 0 To 2 Percent Slopes

Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## KpB2--Keyport Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded

Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## KsC3--Keyport Silty Clay Loam, 5 To 10 Percent Slopes, Severely Eroded

Keyport component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## KsD3--Keyport Silty Clay Loam, 10 To 15 Percent Slopes, Severely Eroded

Keyport component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## Ky--Klej Loamy Sand

Klej component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .17. This soil is somewhat poorly drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 18 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

Ma--Made Land

Madeland component makes up 95 percent of the map unit. The assigned Kw erodibility factor is .43. Available water capacity is very low and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 8s. This component is not a hydric soil.

## MkA--Matapeake Loam, 0 To 2 Percent Slopes

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

## MkB2--Matapeake Loam, 2 To 5 Percent Slopes, Moderately Eroded

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## MkC2--Matapeake Loam, 5 To 10 Percent Slopes, Moderately Eroded

Matapeake component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## MkD--Matapeake Loam, 10 To 15 Percent Slopes

Matapeake component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## MLA--Matapeake Silt Loam, 0 To 2 Percent Slopes

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

## MLB2--Matapeake Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## MLC2--Matapeake Silt Loam, 5 To 10 Percent Slopes, Moderately Eroded

Matapeake component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## MLC3--Matapeake Silt Loam, 5 To 10 Percent Slopes, Severely Eroded

Matapeake component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## MLD3--Matapeake Silt Loam, 10 To 15 Percent Slopes, Severely Eroded

Matapeake component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 6e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

MpA--Mattapex Loam, 0 To 2 Percent Slopes

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## MpB2--Mattapex Loam, 2 To 5 Percent Slopes, Moderately Eroded

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## MxA--Mattapex Silt Loam, 0 To 2 Percent Slopes

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## MxB2--Mattapex Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## My--Mixed Alluvial Land

Mixed Alluvial Land component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .37. This soil is poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is a hydric soil.

## Oh--Othello Silt Loam

Othello component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .37. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

## Ot--Othello Silt Loam, Low

Othello component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .37. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## Pe--Plummer Loamy Sand

Plummer component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .10. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## Pk--Pocomoke Sandy Loam

Pocomoke component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .20. This soil is very poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 0 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## Nontechnical Soil Descriptions--Continued

---

Pm--Pocomoke Loam

Pocomoke component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .20. This soil is very poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 0 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

## Pt--Portsmouth Silt Loam

Portsmouth component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is very poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 6w. This component is a hydric soil.

## SaA--Sassafras Sandy Loam, 0 To 2 Percent Slopes

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

## SaB2--Sassafras Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## SaC2--Sassafras Sandy Loam, 5 To 10 Percent Slopes, Moderately Eroded

Sassafras component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## SaC3--Sassafras Sandy Loam, 5 To 10 Percent Slopes, Severely Eroded

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## SaD--Sassafras Sandy Loam, 10 To 15 Percent Slopes

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## SaD3--Sassafras Sandy Loam, 10 To 15 Percent Slopes, Severely Eroded

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 6e. This component is not a hydric soil.

## SfA--Sassafras Fine Sandy Loam, 0 To 2 Percent Slopes

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

## SfB2--Sassafras Fine Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

SmA--Sassafras Loam, 0 To 2 Percent Slopes

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

## SmB2--Sassafras Loam, 2 To 5 Percent Slopes, Moderately Eroded

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

## SmC2--Sassafras Loam, 5 To 10 Percent Slopes, Moderately Eroded

Sassafras component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## SmC3--Sassafras Loam, 5 To 10 Percent Slopes, Severely Eroded

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## St--Steep Land

Steep Land component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7e. This component is not a hydric soil.

## Tm--Tidal Marsh

Tidal Marsh component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 0 inches. The soil has a moderately saline horizon. It is in nonirrigated land capability class 8w. This component is a hydric soil.

## WdA--Woodstown Sandy Loam, 0 To 2 Percent Slopes

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## WdB2--Woodstown Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## WfA--Woodstown Fine Sandy Loam, 0 To 2 Percent Slopes

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

WoA--Woodstown Loam, 0 To 2 Percent Slopes

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .32. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

## WoB2--Woodstown Loam, 2 To 5 Percent Slopes, Moderately Eroded

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .32. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.



